advanced SAFETY

Butoject® 898



APPLICATION

- > printing industry
- > laboratories
- > manufacturing of paints and varnishes
- > chemical industry
- > metal and plastics processing
- > recycling and waste disposal
- > cleaning and maintenance
- > fire brigades and forces

QUALITIES AND ADVANTAGES

- > very good protection against extremely aggressive chemicals
- > excellent wearing comfort
- > very good temperature flexibility
- > good mechanical resistance
- > high tightness against gas



Article no.	898
Name	Butoject® 898
Material	butyl
Description	rolled edge smooth, powdered
Length (mm)	340-360
Total thickness (mm)	0,7±0,10
Colour	black
Size	8, 9, 10, 11
Classification	Category III EN388 ISO374-I/Iyp A ISO374-5 2111x BCIKLM Virus



FEATURES

- > AQL < 0,65
- > excellent low degradation
- > manufactured by Vulkoject process technology
- > gastight (meets NATO requirements)
- > wide shape makes it possible to wear gloves underneath
- may be reused for certain chemical groups after a special cleaning process (please consult the KCL-laboratory)
- can be combined with chemical protective clothing



www.kcl.de sales@kcl.de



by Honeywell

KCL GmbH

Industriepark Rhoen Am Kreuzacker 9 36124 Eichenzell Germany

Phone +49 6659 87-300 Fax +49 6659 87-318

Honeywell