TEMPCOOK 476

Temperature below 150°C | Wet environments

Hygienic combined with effective thermal protection; 100% fluid-proof

SPECIFIC ADVANTAGES



Thermal protection

• Thermal protection up to 250°C* (* from 150°C, the product can get stiffer and color change may happen, without degrading glove efficiency.)



Durability

Resistance to oils, greases and principal detergent products



Food compliance

• The white/cream colour coding meets the catering industry clothing standards



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



CUT PROTECTION **LEVEL D**

EN388

TYPE A



EN 511:2006



EN ISO 374-1

TYPE A

EN ISO 374-5



AFGJOT



111

EN407



X2XXXX

CATEGORY 3



0334

DEXTERITY

EN ISO 21420: 1/5



INDUSTRIES

- Food industry
- Local Authorities (Catering Services)
- Catering industry
- Bakeries

APPLICATIONS

- Pre-cooking
- Removing dishes from warming ovens
- Removing trays from ovens
- Removing hot dishes from dry or wet ovens
- Removing items from autoclaves and steam ovens



TEMPCOOK 476

Temperature below 150°C | Wet environments

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4 4 4 3 D P Impact protection (optional)

Cut resistance according to ISO

Puncture resistance

Tear resistance

Blade cut resistance


EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



Radiant heat resistant
Convective heat resistance
Contact heat resistance
Limited flame spread

EN 511:2006

COLD HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

 $\frac{1}{0.4} \frac{1}{0.4} \frac{1}{0.1}$

-4 0-4 0/1
| Water permeability
| Contact cold resistance
| Convective cold resistance

EN ISO 374-1

CHEMICAL RISKS A: Methanol



TYPE A

F: Toluene

- G: Diethylamine J: n-Heptane
- O: Ammonia 25%
- T: Formaldehyde 37%

EN ISO 374-5

MICRO-ORGANISMS



Protection against bacteria and fungi



FOOD CONTACT

French decree of 05/08/2020

Edit 07/01/2025

PRODUCT DETAILS

Interior finish	Knitted thermal protection
Exterior finish	Embossed texture
Material	Nitrile
Colour.s	White
Length (cm)	45
European sizes	7 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.6E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	> 3E+13 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 6 pairs/carton

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/19/1095
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

